

PERMANENT FLOW

COMFORTABLE
firewood processing
WITH BINDERBERGER
CONVEYOR BELTS



BELT CONVEYOR *eco*

- // Conveyor length 4,5 m
- // Conveyor height 3,7 m
- // Belt width 25 cm



TYPE	DRIVE	WEIGHT	ARTICLE NO.	PRICE
FB E eco	E-motor 0,75 kW / 400V / 16A	330 kg	FB-MFE-1	2.620,-
FB S eco	Tractor hydraulics (1x double-acting control unit required)	325 kg	FB-MFE-2	2.520,-



BELT CONVEYOR *proline*

- | | | | |
|--------------------|-------|--------------------|-------|
| FB 3 | | FB 5 | |
| // Conveyor length | 4,5 m | // Conveyor length | 7 m |
| // Conveyor height | 3,2 m | // Conveyor height | 5,1 m |
| // Belt width | 40 cm | // Belt width | 40 cm |



TYPE	DRIVE	WEIGHT	ARTICLE NO.	PRICE
FB 3 E proline	E-motor 0,75 kW / 400V / 16A	390 kg	FB-MFP-1	3.650,-
FB 3 S proline	Tractor hydraulics (1x double-acting control unit required)	385 kg	FB-MFP-2	3.550,-
FB 5 E proline	E-motor 0,75 kW / 400V / 16A	800 kg	FB-MFP-3	5.300,-
FB 5 S proline	Tractor hydraulics (1x double-acting control unit required)	800 kg	FB-MFP-4	5.200,-

EQUIPMENT	ARTICLE NO.	PRICE
Hydraulic slewing drive, tractor hydraulics with wireless radio control	FB-ZFP-1	1.530,-

SAW BLADES

for circular saws



TYPE	ARTICLE NO.	PRICE
Chrome steel scalping blade ø 600 mm	KS-ZSB-1	280,-
Chrome steel saw blade ø 700 mm	KS-ZSB-2	110,-
Chrome steel saw blade Hannibal ø 700 mm	KS-ZSB-3	170,-
Hardened metal saw blade, 42 teeth, ø 700 mm	KS-ZSB-4	180,-
Hardened metal saw blade, nail-proof, 84 teeth, ø 700 mm	KS-ZSB-5	220,-
Hardened metal saw blade, 84 teeth, ø 700 mm, for belt conveyor saw <i>proline</i>	KS-ZSB-6	280,-

